

Excel in Your Field™

Specifications

CATEGORY	XR4040	XR4040H	XR4040C	XR4040HC	XR4046	XR4046H	XR4046C	XR4046HC
ENGINE								
Type	4-Cylinder, Indirect-injection, Water-cooled							
Model(Tier4)	ISM N844L-F							
Engine HPI(Gross)	40				46			
PTO HP	32.4	30.8	32.4	30.8	37.3	35.4	37.3	35.4
Rated speed, RPM	2,600							
Displacement-cu, in³	135.2							
Fuel tank capacity(gal)	10.5		12.4		10.5		12.4	
Alternator(V-A)	12 - 85							
DRIVE TRAIN								
Transmission	Synchro shuttle / HST							
No. of Speed	F16 x R16 (Gears) / 3 Ranges (HST)							
Brakes	Wet, Multi - disc							
Steering	Hydrostatic Power Steering							
PTO								
Type	Independent							
Rear(rpm)	540							
Mid PTO(Option)	2,000							
HYDRAULIC SYSTEM								
Control system	Position / Draft							
Implement pump, gpm	8.2							
Steering pump, gpm	4.2 (GEAR), 5.5 (HST)							
Total flow, gpm	12.4 (GEAR), 13.7 (HST)							
Category, 3pt hitch	CAT I							
Hitch Lift capacity, lbs(Hitch end)	2,756							
Remote valves	4 (front), 4 (rear)							
DIMENSION								
Overall length, Bumper to link in.	129.4							
Overall width with tires, in.	62.4							
Wheelbase, in.	69.4							
Ht to top of rops, in.	96.3		91.1		96.3		91.1	
TIRE SIZE								
Ag Front / Rear	9.5 - 16 / 13.6 - 24							
IND Front / Rear	12 - 16.5, 17.5L - 24							
Turf Front / Rear	28x8.5 - 15, 41 x 14 - 20							
WEIGHT								
Total weight without ballast, lbs.	3,870		4,330		3,870		4,330	

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote control valves (2 pair)
- Hydrostatic power steering
- Front loader valve and joystick
- Hydraulic draft and position control
- Adjustable seat
- Extendable lower links and telescopic stabilizers
- Drawbar
- Turn signals
- Safety flashers



LS Tractor USA

LS Tractor USA | 6900 Corporation Parkway, Battleboro, NC
P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

Dealer Imprint Zone

39000939-1311

LS Tractor

XR4000 Series

XR4040 / XR4040H / XR4040C / XR4040HC /
XR4046 / XR4046H / XR4046C / XR4046HC
Premium Compacts



Excel in Your Field™

- Eco-friendly TIER 4 40HP and 46 HP engines
- 5 year warranty*
- 16F x 16R fully synchronized shuttle shift or 3 range HST with cruise control
- Front wheel mechanical assist 4WD
- Choice of industrial, ag or turf tires at no additional cost
- Available with quick attach skid steer compatible front end loader with grill guard
- Available sub frame mounted, quick attach 7' backhoe
- Optional mid-mount PTO

*5-year limited warranty. See dealer for details

XR Series Premium Compacts



Hydrostatic Transmission Models
Maximizes ease of use with effortless, clutch-less and instant speed and directional changes with a simple push of the pedals



Flat platform open station models
With rubber mat and side mounted gear lever, maximizes space, improves operator comfort, and makes getting on/off tractor easier



PTO Switches
Select manual or independent PTO (non HST models only) and turn on or off with a simple turn of switches



Shibaura ISM Tier 4 Engine
Meets EPA's most stringent emission standards while delivering rated horsepower quietly with low vibration



Easy open one-piece hood
provides accessibility for easy maintenance



2 sets of remotes and detent function standard
Adds functionality and improves ease of use by allowing attachment of hydraulically controlled implements without the high, additional costs like others in its class to add the remotes as options



Your choice of tires
Choose ag, industrial or turf tires at no additional cost



Full Function Dash Panel
Important functional data is available at glance for optimum performance and control



Deluxe adjustable seat with retractable seat belt
Keeps you safe and comfortable even during long operations